




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : H04J 3/22, H04Q 11/04	A1	(11) International Publication Number: WO 95/08882 (43) International Publication Date: 30 March 1995 (30.03.95)
(21) International Application Number: PCT/US94/08933 (22) International Filing Date: 8 August 1994 (08.08.94) (30) Priority Data: 08/123,773 20 September 1993 (20.09.93) US (71) Applicant: CODEX CORPORATION, a subsidiary company of MOTOROLA, INC. [US/US]; 20 Cabot Boulevard, Mansfield, MA 02048 (US). (72) Inventors: HLUCHYJ, Michael, G.; 27 Jackson Road, Wellesley, MA 02181 (US). LEE, Whay, Chiou; Westgate Apartments #401, Cambridge, MA 02139 (US). (74) Agents: PARMELEE, Steven, G. et al.; Motorola, Inc., Intellectual Property Dept./DJS, 1303 East Algonquin Road, Schaumburg, IL 60196 (US).		(81) Designated States: AU, CA, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: DYNAMIC RATE ADJUSTMENT FOR OVERLOAD CONTROL IN COMMUNICATION NETWORKS

(57) Abstract

A device and method (300) provide for management of resource allocation on selected links in a connection-oriented communication network such that existing connections may share the burden of freeing up resources for accommodating new connections. The rate of a connection is dynamically adjusted (310, 314), on a connection-by-connection basis, using information (320) on the status of each link broadcast throughout the network. Links are marked (306, 312, 316) based on control information in the link state, and the in-call rate adjustment is based on negotiable quality of service, QOS, parameters.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

BEST AVAILABLE COPY

DYNAMIC RATE ADJUSTMENT FOR OVERLOAD CONTROL IN COMMUNICATION NETWORKS

Field of the Invention

5

This invention is generally directed to capacity overload in a packet network and is more specifically directed to dynamically adjusting a rate of a connection for overload control.

10

Background

In a connection-oriented communication network, the transfer of information between two end-users is accomplished by network functions that select and allocate network resources along an acceptable path. The logical association between the communicating end-users is referred to as a call. The chain of associated network resources that support the call forms a connection. Connection management is a network function that is responsible for setting up, maintaining, and taking down connections. Each call request is issued with a set of quality of service (QOS) requirements that govern the resource allocation for the desired connection. QOS requirements for a connection may be specified in terms of performance constraints (e.g., throughput, delay), resource constraints (e.g., carrier, security), and priority constraints (e.g., establishment priority, retention priority).

Conventional allocation of network resources for connection management is generally static. A fixed level of quality of service, specified by the user, is to be matched at connection setup for a call and must be maintained by best efforts throughout the duration of the call. Certain performance parameters, such as throughput (or rate), are negotiated to determine their respective agreed values. The same agreed values must ideally be met as long as the call is active.

BEST AVAILABLE COPY

Static allocation of network resources is inefficient, and is inadequate for a dynamic networking environment where the user requirements and the quality characteristics of network resources are not static. With user demands that vary with the time of the day, a network is prone to sporadic heavy loads. When network resources (e.g., links) are heavily utilized due to a transient increase of requests for connection establishment and/or re-establishment, time delays and network blocking increase. A network overload control strategy is needed to minimize such degradation in quality of service.

Dynamic routing may be used to steer connections away from saturated links. However, as routing paths meander around saturated links, they tend to be longer. In this respect, more network resources are used, resulting in even higher call blocking rates. A call carried on a long path can potentially block a significant number of other calls that might use the same resources for their connections. Another existing approach is to require incoming calls to wait for connection resources during periods of overload. Although blocking may be somewhat relieved, calls will generally experience a higher delay in connection establishment and re-establishment.

When a link fails, the network attempts to reestablish the affected connections. In a sparsely connected network, a small number of links must share the rerouted traffic. This could lead to an immediate saturation of those links. Many affected connections may thus fail to be reestablished. Those with a high re-establishment priority may still preempt existing connections with a lower retention priority. In any case, some calls would be sacrificed.

A time-of-day call is one that must acquire a connection during a predetermined period of time. In one approach of the prior

BEST AVAILABLE COPY

art, network resources are reserved ahead of time for the time-of-day connection. In order to do that, the network must either add switched facilities when they are needed for the connection, or start accumulating resources for reservation in advance so that enough would be available with a high probability when the resources are needed. In another approach of the prior art, the time-of-day call is assigned a very high establishment priority so that it may acquire the needed resources by preempting existing calls with low retention priority.

Preemptive network resource allocation strategies rely on disruptive retrieval of network resources that have already been allocated to existing calls in order to accommodate new calls of greater importance. Non-preemptive alternatives, such as resource reservation, extended path search, limited waiting for resources, etc., have considerable drawbacks. For voice calls whose rates may be adjusted without affecting the continuing existence of their associated connections, an approach exists that involves the switching between DSI (digital speech interpolation) and non-DSI codings on a network-wide basis. Its control mechanism is strictly triggered by link failures. When there is a link failure, in some devices, every voice call in the network is subject to DSI provided it is permissible. When the failed link is subsequently recovered, the affected voice calls will regain their DSI-free coding.

A different method of dynamically controlling the rate of a connection is found in U.S. Patent No. 5,115,429, "Dynamic Encoding Rate Control Minimizes Traffic Congestion in a Packet Network," by Michael G. Hluchyj and Nanying Yin. This method, known as dynamic rate control, uses a variable rate coder to adjust the source coding rate based on network feedback information. Temporary relief from internodal link congestion resulting in packet queue build-up, and improvement in statistical gain can be realized at the expense of temporarily degrading the quality of service for the connections that are subject to dynamic rate control. In this control scheme,

BEST AVAILABLE COPY

congestion information is picked up and carried by a single bit in the protocol data units (fast packets or cells) and returned to the source by the destination. The source coder switches between a higher rate and a lower rate depending on the feedback information. If the
5 feedback information indicates congestion, the switch is from the higher rate to the lower rate. If the feedback information indicates otherwise, the switch is the opposite. This technique is used for packet level congestion control and operates over time scales on the order of the round trip transmission delay (e.g., 100 msec), whereas
10 the disclosed invention is used for connection-level overload control and operates over much longer time scales (e.g., minutes).

Thus, there is a need for a device and a method that manage
call resource allocation on selected links in a connection-oriented
15 communication network such that existing connections share the burden of releasing resources for accommodating new connections.

20 Brief Descriptions of the Drawings

FIG. 1 is a diagram of connection states in accordance
with the present invention.

25 FIG. 2 is a diagram of examples of marked links.

FIG. 3 shows a flow chart of the steps of a method for
dynamic rate adjustment for overload control in a connection-
oriented communication network in accordance with the
30 present invention.

FIG. 4 shows a flow chart of steps for marking links
based on available link capacity for utilization in the steps of
the method shown in FIG. 3.

35

BEST AVAILABLE COPY

FIG. 5 is a block diagram of an embodiment of a device in accordance with the present invention.

FIG. 6 is a flow chart showing steps of another embodiment of the method of the present invention.

Detailed Description of a Preferred Embodiment

10 The present invention is designed for controlling the load on selected links in a communication network for a variety of traffic management purposes. The invention applies to communication networks that support diverse traffic types, and a variety of user connections including switched connections that are user initiated and generally do not last very long, and permanent connections that are administered by the network operator and must be maintained at all times.

20 For some traffic types, such as voice, the rate for its connection is permitted to vary at the expense of changing the audio quality of the information transferred. This is achievable by using a variable rate coder that adjusts the source coding rate when it is triggered to do so. In addition to a number of possible coding rates, voice traffic also has the option to be subject to speech activity detection and use digital speech interpolation (DSI) to improve its statistical gain.

30 During call setup, a routing function tries to compute a path that satisfies all the QOS constraints, and derives from it an available value for each performance parameter. An acceptable value is specified for each performance parameter such that if the corresponding available value associated with the selected path is less desirable than the acceptable value, the path is not to be used for connection establishment. A performance constraint may be non-negotiable or negotiable. A non-negotiable performance

BEST AVAILABLE COPY

constraint is specified only with the acceptable value. A negotiable performance constraint is specified with a region of values bounded between an acceptable value and a requested value. This region of values is referred to as the agreeable region.

5

For non-negotiable performance constraints, if the available value is at least as desirable as the acceptable value, the acceptable value is taken to be the agreed value, i.e., one that the end-users will accept and the network will support. Each negotiable performance constraint is subject to negotiation that determines an agreed value from within the agreeable region provided an acceptable path is available. During a negotiation, if the available value is more desirable than the requested value, the call may be accepted, but only the requested value would be offered as the agreed value. When the available value falls within the agreeable region, the agreed value is arbitrary as long as it is within the agreeable region as well. For connections that are subject to the dynamic rate adjustment described in this invention, when the available rate falls within the agreeable region, the agreed rate is set to the acceptable rate. Thus, with the present invention, the agreed rate is adjusted to an upper limit (i.e., requested rate) or, alternatively, a lower limit (i.e., acceptable rate).

10
15
20

Dynamic rate adjustment is a novel feature for connection management. FIG. 1, numeral 100, is a connection state diagram in accordance with the present invention. The dynamic rate adjustment transition (112) from the Information Transfer state (114) to itself is a novel element of the present invention.

25
30

When a call arrives (102), it enters the Establishment state (104). If there are not enough resources to support the call (failure to establish - 106), it will be rejected (108). Otherwise, upon successful connection establishment (110) (i.e., a path is available such that all QOS constraints are satisfied), it enters the

35

BEST AVAILABLE COPY

Information Transfer state (114). When a call in the Information Transfer state is completed (124), it enters the Release state (126), and the connection is subsequently taken down (call departure-128). If any QOS degradation leads to a connection failure (117) or the call is preempted (116), the call enters the Re-establishment state (118), so that the network may attempt to reestablish the connection. When a call is in the Re-establishment state (118), the network attempts to find a new acceptable path for connection re-establishment. Upon successful re-establishment (120), the call reenters the Information Transfer state (114). Otherwise (122), it enters the Release state (126) after attempting unsuccessfully to reestablish the connection for a predetermined period that is known as the connection re-establishment delay.

Preemption (116) and blocking of calls (106, 122) when the network is heavily loaded may be minimized if the network is able to partially retrieve allocated resources from existing connections while maintaining their acceptable QOS. For example, the temporary reduction of the rate for an existing permanent connection to make room for an incoming switched connection that does not last long may be quite reasonable.

Dynamic rate adjustment (112) is a connection management procedure for controlling the rates of certain connections in order to free up resources on selected, or marked, links for reallocation. There are a variety of reasons for marking a link. FIG. 2, numeral 200, is a diagram showing examples representing regular links (202, ...) and marked links (204, ...). The examples shown in FIG. 2 are by no means exhaustive. A link may be marked when it is overloaded (link saturation-206) in the sense that the available capacity on the link has fallen below a predetermined threshold. A link may be marked for a period specified by the time-of-day (208). This is useful for freeing up resources in anticipation of the arrival of a time-of-day call such as one for video conferencing. A link may be marked when

BEST AVAILABLE COPY

an adjacent link has failed (204, 210, 212), so that resources are made available for potential rerouted traffic.

The marking of a link is managed by the node that is responsible for monitoring the link's status. A one-bit control information, indicating whether the link is marked or not, is added to the topology update messages broadcast by the node to all other nodes in the network. By using additional bits for the control information, one could communicate multiple levels of link loading in the topology update messages.

The source of each connection, whose rate is subject to dynamic adjustment, examines the path supporting the connection periodically or based on a predetermined event trigger. If at least one link along the path is marked, the rate of the connection is reduced from its previously agreed level to its acceptable level, provided the previously agreed level is higher than the acceptable level. In other words, the agreed rate is adjusted down to the acceptable rate. If all the links along the path are unmarked, the rate of the connection is increased from its previously agreed level to the requested level, provided the previously agreed level is lower than the requested level. The rate is said to be adjusted (increased) from its previously agreed value up to the requested value. In the process of dynamic rate adjustment, the call remains in the Information Transfer state. Note that dynamic rate adjustment does not reroute the connection along a new path. The only change in QOS associated with the connection is the agreed rate.

For example, the dynamic rate adjustment scheme may be implemented based on available capacity. The available capacity associated with a path is the smallest available capacity on any link along the path. When the available capacity is plentiful, the agreed rate is normally permitted to be the same as the requested rate. When the available capacity is small, the agreed rate is normally limited to the acceptable value. If there is only one threshold, the

BEST AVAILABLE COPY

rate adjustment for a connection may suffer from oscillations when the available capacity fluctuates around the threshold. Thus, two thresholds may be used to create a hysteresis effect. For example, the lower threshold may be 20% of link capacity, and the upper threshold may be 30% of link capacity.

FIG. 3, numeral 300, shows a flow chart of the steps of a method for dynamic rate adjustment for overload control in a connection-oriented communication network in accordance with the present invention. The method provides management of call-level resource allocation on selected links such that existing connections share the burden of releasing resources for accommodating new connections. The method includes the steps of: (A) recognizing a dynamic rate adjustment trigger signal (320) that indicates when the source of a given connection must examine the path supporting the connection, (B) determining whether the previously agreed rate associated with the connection is equal to a predetermined requested value (302), and (C) where the previously agreed rate associated with the connection is equal to the predetermined requested value, proceeding through the steps of Group 2 (see below), and (D) where the previously agreed rate associated with the connection is unequal to the predetermined requested value, determining whether the previously agreed rate associated with the connection is equal to a predetermined acceptable value (304). Where the previously agreed rate associated with the connection is equal to the predetermined acceptable value, the steps of Group 1 below are utilized. Where the previously agreed rate associated with the connection is unequal to the predetermined acceptable value (i.e., the previously agreed rate associated with the connection is other than the acceptable and requested values), the steps of Group 3 are utilized.

In Group 1, where the previously agreed rate associated with the connection is equal to a predetermined acceptable value, further steps include determining whether any link along the path supporting

BEST AVAILABLE COPY

- the connection is marked (306) and one of: (1) where at least one link along the path is marked, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, (318), and recycling to step (A) above (determining whether the previously agreed rate associated with the connection is equal to a predetermined requested value (302)), and (2) where all links along the path are unmarked, determining whether a predetermined available capacity associated with the path is greater than or equal to a predetermined requested value (308). In step (2), the steps further include the steps of: (3) where the predetermined available capacity associated with the path is greater than or equal to the requested value, increasing the agreed rate associated with the connection to the requested value (310) and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal (318), and recycling to step (A) above (determining whether the previously agreed rate associated with the connection is equal to a predetermined requested value (302)) and (4) where the predetermined available capacity associated with the path is less than the requested value, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal (318) and recycling to step (A) above (determining whether the previously agreed rate associated with the connection is equal to the requested value (302)).
- 2.5 In Group 2, where the previously agreed rate is equal to a predetermined requested value, further steps include determining whether any link along the path supporting the connection is marked (312) and one of: (1) where all links along the path are unmarked, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal (318) and recycling to step (A) above (determining whether the previously agreed rate associated with the connection equals a predetermined requested value (302)) and (2) where at least one link along the path is marked, reducing the agreed rate associated with the connection to the predetermined acceptable value (314) and returning to the state where the source

BEST AVAILABLE COPY

waits for the arrival of the next rate adjustment trigger signal (318) and recycling to step (A) above (determining whether the previously agreed rate associated with the connection equals a predetermined requested value (302)).

5

In Group 3, where the previously agreed value associated with the connection is a value other than the predetermined requested value and the predetermined acceptable value, further steps include determining whether any link along a path supporting the connection is marked (316) and one of: (1) where all links along the path are unmarked, determining whether the available capacity associated with the path is greater than or equal to the predetermined requested value and, where the available capacity associated with the path is less than the predetermined requested value, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal (318) and recycling to step (A) above (determining whether the previously agreed rate associated with the connection equals a predetermined requested rate (302)), and where the available capacity associated with the path is greater than or equal to the requested value, increasing the rate to the requested value (310) and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal (318), and recycling to step (A) above (determining whether the previously agreed rate associated with the connection equals a predetermined requested rate (302)), and (2) where at least one link along the path is marked, reducing the agreed rate associated with the connection to the predetermined acceptable value (314) and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal (318) and recycling to step (A) above (determining whether the previously agreed rate associated with the connection equals a predetermined requested value (302)).

Note that the agreed, acceptable, and requested values for the rate are associated with a connection or the path that supports the connection, not simply a single link. The agreed value associated

35

BEST AVAILABLE COPY

with a call for the method shown in FIG. 3 is initially determined by means of a negotiation procedure, utilizing the steps of: (1) where the available capacity associated with the path is greater than a predetermined requested value, setting the agreed value to the predetermined requested value, (2) where the available capacity associated with the path is less than the predetermined requested value but not less than a predetermined acceptable value, setting the agreed value to the predetermined acceptable value, and (3) where the available capacity associated with the path is less than the predetermined acceptable value, the call is rejected. During rate adjustment, the previously agreed rate may be adjusted to a new agreed rate. When the next rate adjustment is needed, the new agreed rate set by the previous rate adjustment becomes the previously agreed rate for the current rate adjustment.

15

FIG. 4, numeral 400, shows a flow chart of steps for marking a given link based on available link capacity for utilization in the steps of the method shown in FIG. 3. The status of each link is monitored by a predetermined node. Where a new connection arrives at a given link (403) (i.e., resource of the given link are allocated to a new connection), the connection bandwidth is subtracted from the predetermined available link capacity to determine an adjusted available link capacity (AALC)(404), and the node that monitors the link's status determines whether the link is marked (406). Where the link is marked, the node returns to a waiting mode (402), and, where the link is unmarked, the node determines whether the AALC is less than a predetermined lower threshold (PLT) (408). Where the AALC is greater than a predetermined lower threshold (PLT) (408), the node returns to the waiting mode (402). Where the AALC is less than or equal to a predetermined lower threshold (PLT) (408), the node marks the link (410) and returns to the waiting mode (402). Where an existing connection departs from a link, the node that monitors the link's status adds the connection bandwidth from the predetermined available link capacity to determine the adjusted available link capacity (AALC) (412) and determines whether the

35

BEST AVAILABLE COPY

link is marked (414). Where the link is unmarked, the node returns to a waiting mode (402). Where the link is marked, the node determines whether the AALC is greater than or equal to a predetermined upper threshold (PUT) (416). Where the AALC is less than a predetermined upper threshold (PUT) (416), the node returns to the waiting mode (402). Where the AALC is greater than or equal to the PUT, the node unmarks the link (418) and returns to the waiting mode (402).

FIG. 5 is a block diagram of an embodiment of a device in accordance with the present invention. The device provides dynamic rate adjustment for overload control in a connection-oriented communication network by managing call-level resource allocation on selected links such that existing connections share the burden of releasing resources for accommodating new connections. The device includes a rate adjustment determiner (502) and a rate adjustment controller (504).

The rate adjustment determiner (502) is operably coupled to the rate adjustment controller (504). Upon the arrival of a rate adjustment trigger signal, indicating that it is time for the source associated with the connection to attempt rate adjustment, the rate adjustment determiner determines if rate adjustment is needed, and if so, determines a new agreed rate for the connection. The rate adjustment controller (504) is operably coupled to the rate adjustment determiner (502). The rate adjustment controller (504) changes the previously agreed rate to the new agreed rate determined by the rate adjustment determiner. The new (or adjusted) agreed rate becomes the input (i.e., previously agreed rate) to the rate adjustment determiner when the next rate adjustment trigger signal arrives. The rate adjustment trigger is basically a mechanism that issues a rate adjustment request (trigger signal) to the rate adjustment determiner whenever a predetermine event occurs. For example, the event may be the expiration of a timer,

BEST AVAILABLE COPY

which is reset each time after a rate adjustment attempt is completed.

When rate adjustment is being considered, the rate adjustment determiner (502) determines a new agreed rate such that, where the previously agreed rate is equal to a predetermined acceptable value, the rate adjustment determiner determines whether any link along the path of the connection is marked and one of: (1) where at least one link along the path of the connection is marked, returns to the state where the source waits for the arrival of the next rate adjustment trigger signal, and (2) where all links along the path of the connection are unmarked, determines whether a predetermined available capacity associated with the path is greater than or equal to a predetermined requested value. Where the predetermined available capacity associated with the path is greater than or equal to the requested value, the rate adjustment determiner (502) signals the rate adjustment controller to increase the agreed rate to the requested value, and then returns to the state where the source waits for the arrival of the next rate adjustment trigger signal. Where the predetermined available capacity associated with the path is less than the predetermined requested value, the rate adjustment determiner determines that the previously agreed value is to be maintained, and then returns to the state where the source waits for the arrival of the next rate adjustment trigger signal.

25

The rate adjustment determiner (502) determines a new agreed rate such that, where the previously agreed rate is equal to a predetermined requested value, the rate adjustment determiner (502) determines whether any link along the path of the connection is marked and one of: (1) where all links along the path of the connection are unmarked, returns to the state where the source waits for the arrival of the next rate adjustment trigger signal, and (2) where at least one link along the path of the connection is marked, signals the rate adjustment controller (504) to reduce the agreed rate to a predetermined acceptable value, and then returns to

BEST AVAILABLE COPY

the state where the source waits for the arrival of the next rate adjustment trigger signal.

The rate adjustment determiner (502) determines a new
5 agreed rate such that, where the previously agreed rate is a value other than the predetermined requested value and the predetermined acceptable value, the rate adjustment determiner (502) determines whether any link along the path of the connection is marked and one
10 of: (1) where all links along the path of the connection are unmarked and the available capacity associated with the path is greater than the requested value, signals the rate adjustment controller (504) to increase the agreed rate to the requested value, and then returns to the state where the source waits for the arrival of the next rate
adjustment trigger signal, and (2) where all links along the path of
15 the connection are unmarked and the available capacity associated with the path is less than the requested value, leaves the agreed rate unchanged, and then returns to the state where the source waits for the arrival of the next rate adjustment trigger signal. Where at least one link along the path of the connection is marked, the rate
20 adjustment determiner (502) signals the rate adjustment controller (504) to reduce the agreed rate to the acceptable value, and then returns to the state where the source waits for the arrival of the next rate adjustment trigger signal.

25 In the device of the present invention, the agreed rate is determined as set forth above in the method. A link is marked by a predetermined node that monitors its status.

FIG. 6, numeral 600, is a flow chart showing steps of another
30 embodiment of the method of the present invention. The method for, upon receiving a rate adjustment trigger signal, dynamic rate adjustment for overload control in a connection-oriented communication network by managing call-level resource allocation on selected links such that existing connections share the burden of
35 releasing resources for accommodating new connections, includes

BEST AVAILABLE COPY

the steps of: (A) utilizing a rate adjustment determiner, upon receiving a rate adjustment trigger signal, to determine a new agreed rate for a connection (602), and (B) utilizing a rate adjustment controller to adjust the previously agreed rate according to the new agreed rate determined by the rate adjustment determiner, provided that the new agreed rate is different from the previously agreed rate, and then recycling to step (A) (604). Determination of the new agreed rate for the connection is described in more detail above.

10

The invention is different from the prior art of dynamic rate control in a few aspects. Dynamic rate control manages packet level congestion, whereas the invention is used to manage call level overload. While dynamic rate control is a congestion control scheme that imposes restraint on the sources after congestion is detected, the invention, implemented based on marking saturated links, is an overload avoidance scheme that imposes restraint on the sources normally before link saturation actually occurs. The invention is not limited to addressing overload or congestion control issues.

20

Although exemplary embodiments are described above, it will be obvious to those skilled in the art that many alterations and modifications may be made without departing from the invention. Accordingly, it is intended that all such alterations and modifications be included within the spirit and scope of the invention as defined in the appended claims.

25

We claim:

BEST AVAILABLE COPY

1. A device for dynamic rate adjustment for overload control in a connection-oriented communication network by managing call-level resource allocation on selected links such that existing connections share the burden of releasing resources for accommodating new connections, comprising:

A) a rate adjustment determiner, operably coupled to a rate adjustment controller, for, upon receiving a rate adjustment trigger signal, determining a new agreed rate for the connection and providing the new agreed rate to the rate adjustment controller, and

B) the rate adjustment controller, operably coupled to the rate adjustment determiner, for adjusting the previously agreed rate to a new agreed rate determined by the rate adjustment determiner.

BEST AVAILABLE COPY

2. The device of claim 1 wherein the rate adjustment determiner determines a new agreed rate such that:

5 A) where the previously agreed rate is equal to a predetermined acceptable value, the rate adjustment determiner determines whether any link along a path supporting the connection is marked and one of B1-B2:

B1) where at least one link is marked, leaving the previously agreed rate unchanged,

10 B2) where all links along the path are unmarked, determines whether a predetermined available capacity associated with the path is greater than or equal to a predetermined requested value and one of B2a-B2b:

15 B2a) where the predetermined available capacity associated with the path is greater than or equal to the requested value, determines that the new agreed rate is equal to the requested value, and signals the rate adjustment controller to adjust the agreed rate accordingly,

20 B2b) where the predetermined available capacity associated with the path is less than the requested value, leaving the previously agreed rate unchanged,

C) where the previously agreed rate is equal to a predetermined requested value, the rate adjustment determiner determines whether any link along a path supporting the connection is marked and one of C1-C2:

25 C1) where all links along the path are unmarked, leaving the previously agreed rate unchanged,

C2) where at least one link is marked, determines that the new agreed rate is equal to a predetermined acceptable value, and signals the rate adjustment controller to adjust the agreed rate accordingly,

30 D) where the previously agreed rate is a value other than a predetermined requested value and a predetermined acceptable value, the rate adjustment determiner determines whether any link along a path supporting the connection is marked and one of D1-D3:

BEST AVAILABLE COPY

D1) where all links along the path are unmarked and the available capacity associated with the path is less than the requested value, leaving the previously agreed rate unchanged,

5 D2) where all links along the path are unmarked and the available capacity associated with the path is greater than or equal to the requested value, determines that the new agreed rate is equal to the requested value, and signals the rate adjustment controller to adjust the agreed rate accordingly,

10 D3) where at least one link is marked, determines that the new agreed rate is equal to the acceptable value, and signals the rate adjustment controller to adjust the agreed rate accordingly.

3. The device of claim 2 wherein a new agreed rate is determined
15 utilizing the steps of one of 3A-3B:

3A) where the available capacity associated with the path is greater than or equal to a predetermined requested value, setting the agreed rate to the requested value,

20 3B) where the available capacity associated with the path is less than a predetermined requested value, leaving the agreed rate unchanged.

4. The device of claim 2 wherein a predetermined node marks a given link based on available capacity such that at least one of A-B:

25 A) where a new connection arrives at the given link, the predetermined node subtracts the connection bandwidth from the predetermined available link capacity to determine an adjusted available link capacity (AALC), determines whether the link is marked and one of A1-A2:

30 A1) where the link is marked, returns to a waiting mode,

A2) where the link is unmarked, determines whether the AALC is less than a predetermined lower threshold (PLT) and one of A2a and A2b:

BEST AVAILABLE COPY

A2a) where the AALC is greater than the PLT, returns to the waiting mode,

A2b) where the AALC is less than or equal to the PLT, marks the link and returns to the waiting mode,

5 and

B) where an existing connection departs from the given link, the predetermined node adds the connection bandwidth from the predetermined available link capacity to determine the adjusted available link capacity (AALC), determines whether the link is marked and one of B1 and B2:

10

B1) where the link is unmarked, returns to a waiting mode,

B2) where the link is marked, determines whether the AALC is less than a predetermined upper threshold (PUT) and one of B2a and B2b:

15

B2a) where the AALC is less than the PUT, returns to the waiting mode,

B2b) where the AALC is greater than or equal to the PUT, unmarks the link and returns to the waiting mode.

20

BEST AVAILABLE COPY

5. A method for dynamic rate adjustment for overload control in a connection-oriented communication network by managing call-level resource allocation on selected links such that existing connections share the burden of releasing resources for accommodating new connections, comprising the steps of:
- 5 A) selecting a new agreed rate for a connection upon receiving a rate adjustment trigger signal, utilizing the steps of one of B-D, and recycling to step A upon completion of a rate adjustment cycle,
- 10 B) where the previously agreed rate is equal to a predetermined acceptable value, determining whether any link along the path supporting the connection is marked and one of B1-B2:
- B1) where at least one link is marked, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and completing the rate adjustment cycle,
- 15 B2) where all links along the path are unmarked, determining whether a predetermined available capacity associated with the path is greater than or equal to a predetermined requested value and one of B2a-B2b:
- 20 B2a) where the predetermined available capacity associated with the path is greater than or equal to the requested value, increasing the agreed rate associated with the connection to the requested value, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and completing the rate adjustment cycle,
- 25 B2b) where the predetermined available capacity associated with the path is less than the requested value, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and completing the rate adjustment cycle,
- 30 C) where the previously agreed rate is equal to a predetermined requested value, determining whether any link along a path supporting the connection is marked and one of C1-C2:

REST AVAILABLE COPY

C1) where all links along the path are unmarked, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and completing the rate adjustment cycle,

5 C2) where at least one link is marked, reducing the agreed rate associated with the connection to a predetermined acceptable value and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and completing the rate adjustment cycle,

10 D) where the previously agreed rate is a value other than a predetermined requested value and a predetermined acceptable value, determining whether any link along a path supporting the connection is marked and one of D1-D2:

D1) where all links along the path are unmarked,
15 determining whether the available capacity associated with the path is greater than or equal to the requested value and, where the available capacity associated with the path is less than the requested value, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and
20 completing the rate adjustment cycle, and where the available capacity associated with the path is greater than or equal to the requested value, increasing the agreed rate associated with the connection to the requested value and returning to the state where the source waits for the arrival of the next rate adjustment trigger
25 signal, and completing the rate adjustment cycle,

D2) where at least one link along the path is marked, reducing the agreed rate associated with the connection to the acceptable value and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal, and
30 completing the rate adjustment cycle.

BEST AVAILABLE COPY

6. The method of claim 5 wherein a new agreed rate is determined utilizing the steps of one of 6A-6B:

6A) where the available capacity associated with the path is greater than a predetermined requested value, setting the new
5 agreed rate to the requested value,

6B) where the available capacity associated with the path is less than a predetermined requested value, leaving the agreed rate unchanged.

10 7. The method of claim 5 wherein further including the step of marking links based on available capacity such that:

A) where a new connection arrives at a link,

A1) subtracting the connection bandwidth from the predetermined available link capacity to determine an adjusted
15 available link capacity (AALC),

A2) determining whether the link is marked and one of
20 A2a and A2b:

A2a) where the link is marked, returning to a waiting mode,

20 A2b) where the link is unmarked, determining whether the AALC is less than or equal to a predetermined lower threshold (PLT) and one of A2b1 and A2b2:

A2b1) where the AALC is greater than or the PLT, returning to the waiting mode,

25 A2b2) where the AALC is less than or equal to the PLT, marking the link and returning to the waiting mode, and

B) where an existing connection departs from a link,

30 B1) adding the connection bandwidth from the predetermined available link capacity to determine the adjusted available link capacity (AALC),

B2) determining whether the link is marked and one of B2a and B2b:

35 B2a) where the link is unmarked, returning to a waiting mode,

BEST AVAILABLE COPY

B2b) where the link is marked, determining whether the AALC is less than a predetermined upper threshold (PUT) and one of B2b1 and B2b2:

- B2b1) where the AALC is less than the PUT,
- 5 returning to the waiting mode,
- B2b2) where the AALC is greater than or equal to the PUT, unmarking the link and returning to the waiting mode.

BEST AVAILABLE COPY

8. A method for dynamic rate adjustment for overload control in a connection-oriented communication network by managing call resource allocation on selected links such that existing connections share the burden of releasing resources for accommodating new connections, comprising the steps of:

8A) utilizing a rate adjustment determiner to determine a new agreed rate for a connection upon receiving a rate adjustment trigger signal, and

8B) utilizing a rate adjustment controller to adjust the previously agreed rate to the new agreed rate determined by the rate adjustment determiner, provided that the new agreed rate is different from the previously agreed rate, and then recycling to step (8A).

BEST AVAILABLE COPY

9. The method of claim 8 wherein the rate adjustment determiner determines a new agreed rate, upon receiving a rate adjustment trigger signal, utilizing the steps of:

5 A) where the previously agreed rate is equal to a predetermined acceptable value, determining whether any link along a path supporting the connection is marked and one of B1-B2:

B1) where at least one link along the path is marked, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

10 B2) where all links along the path are unmarked, determining whether a predetermined available capacity associated with the path is greater than or equal to a predetermined requested value and one of B2a-B2b:

15 B2a) where the predetermined available capacity associated with the path is greater than or equal to the predetermined requested value, increasing the agreed rate associated with the connection to the predetermined requested value and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

20 B2b) where the predetermined available capacity associated with the path is less than the predetermined requested value, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

25 C) where the previously agreed rate is equal to a predetermined requested value, determining whether any link along a path supporting the connection is marked and one of C1-C2:

C1) where all links along the path are unmarked, returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

30 C2) where at least one link is marked, reducing the agreed rate to a predetermined acceptable value and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

35 D) where the previously agreed rate is a value other than a predetermined requested value and a predetermined acceptable

BEST AVAILABLE COPY

value, determining whether any link along a path supporting the connection is marked and one of D1-D3:

5 D1) where all links along the path are unmarked and the available capacity associated with the path is less than the requested value, leaving the agreed rate unchanged and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

10 D2) where all links along the path are unmarked and the available capacity associated with the path is greater than or equal to the requested value, increasing the agreed rate associated with the connection to the requested value and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal,

15 D3) where at least one link along the path is marked, reducing the agreed rate associated with the connection to the predetermined acceptable value and returning to the state where the source waits for the arrival of the next rate adjustment trigger signal.

20 10. The method of claim 9 wherein a new agreed rate is determined utilizing the steps of one of 10A-10B:

10A) where the available capacity associated with the path is greater than a predetermined requested value, setting the agreed rate to the requested value,

25 10B) where the available capacity associated with the path is less than a predetermined requested value, leaving the previously agreed rate unchanged.

30 11. The method of claim 9 including the step of a predetermined node marking links based on available capacity such that at least one of A-B:


A) where a new connection arrives at a link, the predetermined node subtracting the connection bandwidth from the predetermined available link capacity to
35 determine an adjusted available link capacity (AALC)

BEST AVAILABLE COPY

- and determining whether the link is marked and one of A1-A2:
- A1) where the link is marked, returning to a waiting mode,
 - A2) where the link is unmarked, determining whether the AALC is less than or equal to a predetermined lower threshold (PLT) and one of A2a and A2b:
 - A2a) where the AALC is greater than the PLT, returning to the waiting mode,
 - A2b) where the AALC is less than or equal to the PLT, marking the link and returning to the waiting mode,
 - and
 - B) where an existing connection departs from a link, the predetermined node adding the connection bandwidth from the predetermined available link capacity to determine the adjusted available link capacity (AALC) and determining whether the link is marked and one of B1 and B2:
 - B1) where the link is unmarked, returning to a waiting mode,
 - B2) where the link is marked, determining whether the AALC is less than a predetermined upper threshold (PUT) and one of B2a and B2b:
 - B2a) where the AALC is less than the PUT, returning to the waiting mode,
 - B2b) where the AALC is greater than or equal to the PUT, unmarking the link and returning to the waiting mode.

BEST AVAILABLE COPY

1/5

100**FIG. 1****BEST AVAILABLE COPY**

2 / 5




FIG. 2

BEST AVAILABLE COPY




FIG. 3

BEST AVAILABLE COPY

4 / 5

400






FIG. 4

BEST AVAILABLE COPY

5/5

*FIG. 5**FIG. 6*

INTERNATIONAL SEARCH REPORT

In: ational application No.
PCT/US94/08933

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) :H04J 3/22; H04Q 11/04

US CL :370/32.1, 60, 84

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 370/32.1, 60, 84, 54, 79, 95.1, 95.3

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US, A, 5,007,047 (SRIDHAR et al.) 09 April 1991, col. 13, lines 26-48, col. 18, lines 30-32, 56-66, col. 19, lines 3-6.	1, 8 ----- 2-7, 9-11
Y	US, A, 5,023,869 (GROVER et al.) 11 June 1991, col. 13, line 5 to col. 14, line 49, col. 23 lines 32-50.	2-7, 9-11
Y,P	US, A, 5,276,677 (RAMAMURTHY et al.) 04 January 1994, col. 14, lines 3-7.	4, 7, 11
A,P	US, A, 5,301,191 (OTANI) 05 April 1994, entire document.	1-11

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be part of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Z" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 07 OCTOBER 1994	Date of mailing of the international search report 15 DEC 1994
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230	Authorized officer <i>Shane Sauls</i> DOUGLAS OLMS Telephone No. (703) 305-4703

Form PCT/ISA/210 (second sheet)(July 1992)*

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

In ational application No.
PCT/US94/08933

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 3,639,693 (BARTLETT et al.) 01 February 1972, entire document.	1-11

Form PCT/ISA/210 (continuation of second sheet)(July 1992)*

BEST AVAILABLE COPY

THIS PAGE BLANK (USPTO)